


# INR-420

## 200-Channel 8-Bay RAID Rackmount Standalone NVR




- 8-bay Rackmount (2U) with hardware RAID (0,1, 5, 10)
- Manage up to 200 cameras or video encoders
- Recording up to 200 Channels
- Live view local up to 16-channel, remote up to 81-channel
- Synchronized playback local up to 9-channel, remote up to 64-channel
- Export video with RAW and AVI formats
- Event trigger, response and notification
- Mobile Client, Web Client, Workstation
- Location-based management with eMap
- 200-channel free license included
- Non-ACTi camera support via licensed Camera Device Pack

### PHOTO INDICATION




### DIMENSION DIAGRAM



### SOLUTION ARCHITECTURE

#### Standalone NVR



**PRODUCT SPECIFICATION****INR-420****• General**

Full Name	ACTi Standalone Network Video Recorder INR-420
Maximum Number of Clients	1 local, 3 remote
Maximum Number of Cameras	200
Free License	200 Channels
Compression	H.264, MPEG-4, MJPEG
Maximum local display resolution	1920 x1080

**• Live View**

Display Layout Mode	Local: 1, 4, 5, 6, 8, 9, 10, 12, 16 Remote: 1, 4, 5, 6, 8, 9, 10, 12, 16, 18, 24, 25, 35, 36, 48, 49, 64, 81
View Manager	An interface to define display layouts and the pre-set cameras within layout in the public or private view
View Patrol	Automatic switch between different views or devices
View Panel	Contains the list of pre-defined views for quick launch
Digital Zoom	Zoom in/out digitally by PiP (Picture-in-Picture)
Camera Tree	Drag and drop video source from camera tree into display layout; display camera status on the tree
Manual Recording / Snapshot	Instant recording upon mouse click / Instant snapshot upon mouse click or hot key
Event Panel	Display event status upon alarm or upon connection loss or recovery
Two-way Audio	Audio sound from and to all the audio supported devices; audio broadcast to multiple devices at the same time
Dual Stream Management	Live view of stream 1 or stream 2 of dual stream devices
Instant Playback	Instant playback in live view window

**• e-Map**

Layout	Area maps with camera icons, small live view windows; hyperlinked
Map Switch and Tour	Manual switch and auto tour modes selectable
Setup	e-Map image upload; camera positioning; map linking
PTZ Mode	Mouse PTZ mode to control e-Map video streams

**• PTZ**

Control	Pan, tilt and zoom controls; speed control; both buttons and mouse controls
Preset Points and Tours	Create preset points; create auto tours between preset points
Number of Preset Points	32
Joystick	USB based joystick supported
Default Protocol	Auto-detect camera's PTZ protocol. Available protocols: ACTi, Pelco-P, Pelco-D, Dynacolor, Visca

**• Recording**

Recording Throughput	Maximum total bitrate 300 Mbps Example: 200 Channels: 1MP, 15fps, H.264, 1.5Mbps 150 Channels: 2MP, 15fps, H.264, 2Mbps 100 Channels: 2MP, 30fps, H.264, 3Mbps 75 Channels: 5MP, 15fps, H.264, 4Mbps
Scheduled Recording	Record video with user defined schedule
Event Recording	Record video when the alarm event is triggered, including the pre-event buffered video clip
Speed Up	Different recording frame rate settings for non-event and triggered event
Manual Recording	Instant recording upon mouse click
Dual Stream Management	Recording of stream 1 or stream 2 of dual stream devices
Recording Frame Rate	Max 6000 fps total; Max 30 fps per camera

**• Storage**

Interface	Serial ATA
Bundled System HDD	Seagate 500GB 3.5" SATA HDD
HDD Bay	8 (1 bay is occupied by system HDD)
RAID Level	Hardware RAID 0, 1, 5, 10
External Storage Support	eSATA, iSCSI, USB mass storage (USB 2.0)

**• Search & Playback**

Time Based Video Search	Search video recordings by time or channel
Event Based Video Search	Search alarm triggered video recordings
Playback Control	Continuous forward and backward playback with speeds 1x/2x/4x/8x or frame-by-frame; pause; stop
Synchronized Playback	Up to 9 channels for local display; up to 64 channels for remote client
Manual Snapshot	Instant snapshot from playback upon mouse click
Digital Zoom	Zoom in/out digitally by PiP (Picture-in-Picture)
Video Cropping	Crop a short video clip from long recording file and save it as an independent file
Video Export	Export video clips in AVI or RAW format; text overlay supported

**• Event Management**

Event Trigger	Video motion detection; Passive IR sensor; External device through digital input; Video loss and recovery; Network loss and recovery; Server loss and recovery; Disk full; Disk not found
Event Response	Record video; Pop-up window with live video; Switch to hotspot window; Play beep sound; Activate external device through digital output; Upload snapshot to FTP server; Execute system command to activate other programs; E-mail notification with snapshots; Command a PTZ device to go to a preset point
Manual Event Scheduler	Manually activate external devices through digital output via live view monitor Define the schedule of event manager

\* All specifications are subject to change without notice.

\* All brand names and registered trademarks are the property of their respective owners.

www.acti.com



# INR-420

## • System

Permission Control	Multi-group/users, liveview/playback/setup/remote level permission
Operating System	Windows Embedded Standard 7
Language	Multi-language support

## • Remote Access

PC Client Program	User interface program (Workstation) with live view, PTZ, playback, e-Map, event management, setup
PC Web Browser	Microsoft Internet Explorer 8.0, 9.0 or 10.0 with live view, PTZ, playback, event management, setup
Mobile Client Program	Mobile device application (Active Mobile Client) supports live view, PTZ control, event or time based search and playback Supported devices: iPhone, iPad, iTouch and Android device
Remote Client PC System Requirement	1-16 channels: Intel Core 2 Quad 2.4GHz, 4GB RAM 17-81 channels: Intel Core i7-920 2.67 GHz, 4GB RAM

## • Hardware

CPU	Intel Processor
RAM	8GB
Dimensions (W x H x D)	889 mm x 437 mm x 5334 mm (3.5" x 17.2" x 21")
Weight	11.42kg (with HDD*1 & front bezel)
Operating Temperature	0°C~ 40°C (32°F ~ 104°F)
Operating Humidity	10% ~ 85% RH
Power Source / Consumption	110V~220V AC 50/60Hz / 85 W
Approvals	CE (EN 55022 Class B, EN 55024), FCC (Part15 Subpart B Class B)
USB	USB 2.0, 8 ports (2 front ports, 6 rear ports)
Ethernet Port	2, Gigabit Ethernet ports (1000 Base-T), RJ-45 connector
eSATA Port	1
Display port	2 HDMI, 1 VGA

## • Integration

Unified Solution	Fully compatible with ACTi cameras, encoders and CMS2.0
------------------	---